BENE 10F MOB

72 variants



Dimensions

BENE 10F MOB

Available colours

White **Black**

BENE 10F MOB is a recessed LED ceiling luminaire made of aluminium. The body has a length of 298 mm, width of 62 mm and height of 50 mm. Its recessed installation keeps the room free of projecting fittings and suits homes, hospitality interiors and commercial spaces that call for a clean ceiling. The available 15°, 30° and 38° beams offer a choice from concentrated accent lighting to wider coverage. The 2700, 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. It is available in white and black finishes. Control is available through On-Off and DALI2, with Casambi available in the corresponding version, to suit the lighting control requirements of the project. The construction is rated IP20 with an impact rating of IK04.

LUMINAIRE POWER

18 W

LUMINAIRE LUMINOUS FLUX

1,710 - 1,890 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of BENE 10F MOB.

Mounting position	**Ceiling Recessed**	Control Gear	**Remote Electronic Driver**
Housing	**Aluminium**	Operating voltage	**230 V**
Light source	**SMD LED**	Protection rating	**IP20 / IK04**
Body dimensions	**62 × 298 × 50 mm**		
Markings and catalogue references	**CE**		

Options per version

Beams 15° (N), 30° (M), 38° (W) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 95 - 105 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K	15°, 30°, 38°	18	**1,710**
930	3000 K	15°, 30°, 38°	18	**1,800**
935	3500 K	15°, 30°, 38°	18	**1,845**
940	4000 K	15°, 30°, 38°	18	**1,890**

Luminous flux range per version

Minimum 1,710 lm / 18 W / 927 / DL5644CL001ON

Maximum 1,890 lm / 18 W / 940 / DL5650CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >