BRUTUS

90 variants



Dimensions



Available colours

White **Black** **Grey** **Anthracite** **Dark brown**

BRUTUS is an LED lighting bollard made of aluminium. The body has a diameter of 180 mm. It is offered in 600 and 1000 mm heights, allowing the size to be selected for the application. Its ground-level placement helps organise lighting along paths, around planting and near entrances. It can be used individually or repeated to follow the layout of the outdoor space. The polycarbonate optical surface is UV resistant. The 2700, 3000 and 4000 K options with CRI80 allow the lighting to match the colour appearance required in the space. It is available in dark brown, anthracite, black, white and grey finishes. Control is available through On-Off and DALI2, with Casambi available in the corresponding version, to suit the lighting control requirements of the project. The construction is rated IP65 with an impact rating of IK09.

LUMINAIRE POWER

20 W

LUMINAIRE LUMINOUS FLUX

960 - 1,058 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of BRUTUS.

Mounting position	**Bollard**	Control Gear	**Built-in ECG**
Housing	**Aluminium**	Operating voltage	**230 V**
Optic	**UV-resistant polycarbonate**	Protection rating	**IP65 / IK09**
Light source	**SMD LED**	Insulation class	**Class II**
Markings and catalogue references	**CE**		

Options per version

Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 48 - 52.9 lm/W | Height 600 - 1,000 mm | Diameter 180 mm

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
827	2700 K		20	**960**
830	3000 K		20	**1,008**
840	4000 K		20	**1,058**

Luminous flux range per version

Minimum 960 lm / 20 W / 827 / BO0448CL152ON

Maximum 1,058 lm / 20 W / 840 / BO0452CL152ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >