BRUTUS M

96 variants



Dimensions



Available colours

White **Black** **Dark Grey** **Silver**

BRUTUS M is an LED lighting bollard made of aluminium. The body has a diameter of 100 mm. It is offered in 350 and 750 mm heights, allowing the size to be selected for the application. Its ground-level placement helps organise lighting along paths, around planting and near entrances. It can be used individually or repeated to follow the layout of the outdoor space. The 3000 and 4000 K options with CRI80 allow the lighting to match the colour appearance required in the space. It is available in silver, dark grey, black and white finishes. Control is available through On-Off and DALI2, with Casambi available in the corresponding version, to suit the lighting control requirements of the project. The construction is rated IP65 with an impact rating of IK10.

LUMINAIRE POWER

6.5 - 12 W

LUMINAIRE LUMINOUS FLUX

324 - 608 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of BRUTUS M.

Mounting position	**Bollard**	Control Gear	**Built-in ECG**
Housing	**Aluminium**	Operating voltage	**230 V**
Light source	**SMD LED**	Protection rating	**IP65 / IK10**

Markings and catalogue references	**CE**

Options per version

Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 49.9 - 50.7 lm/W | Height 350 - 750 mm | Diameter 100 mm

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
830	3000 K		6.5 - 12	**324 - 608**
840	4000 K		6.5 - 12	**324 - 608**

Luminous flux range per version

Minimum 324 lm / 6.5 W / 830 / BO0454CL155ON

Maximum 608 lm / 12 W / 830 / BO0456CL155ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >