CERVA 3 INGROUND

9 variants



Dimensions



Available colours

Inox

CERVA 3 INGROUND is a recessed LED ground luminaire made of stainless steel and aluminium. The body has a diameter of 25 mm and height of 67 mm. The recessed installation integrates the fitting into paving and landscape layouts. It provides a lighting point for nearby surfaces and features while keeping the body visually unobtrusive above ground. The available 15°, 24° and 36° beams offer a choice from concentrated accent lighting to wider coverage. The 2700, 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. The finish is stainless steel. The construction is rated IP67.

LUMINAIRE POWER

2 W

LUMINAIRE LUMINOUS FLUX

78 - 98 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of CERVA 3 INGROUND.

Mounting position	**Floor Recessed**	Operating voltage	**24 V**
Housing	**Stainless steel / Aluminium**	Protection rating	**IP67**
Light source	**SMD LED**	Lighting direction	**Upwards**
Body dimensions	**Ø 25 × 67 mm**	Accessories	**HONEY COMB**
Control Gear	**Remote Electronic Driver**		

Options per version

Beams 15° (N), 24° (M), 36° (W) | Control On-Off

Luminous efficacy 39 - 49 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K	15°, 24°, 36°	2	**78**
930	3000 K	15°, 24°, 36°	2	**88**
940	4000 K	15°, 24°, 36°	2	**98**

Luminous flux range per version

Minimum 78 lm / 2 W / 927 / GR0398CL135ON

Maximum 98 lm / 2 W / 940 / GR0404CL135ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >