
CERVA 5 INGROUND

9 variants



Dimensions



Available colours

Inox

CERVA 5 INGROUND is a recessed LED ground luminaire made of stainless steel and aluminium. The body has a diameter of 50 mm and height of 90 mm. The recessed installation integrates the fitting into paving and landscape layouts. It provides a lighting point for nearby surfaces and features while keeping the body visually unobtrusive above ground. The available 15°, 24° and 36° beams offer a choice from concentrated accent lighting to wider coverage. The 2700, 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. The finish is stainless steel. The construction is rated IP67.

LUMINAIRE POWER

3 W

LUMINAIRE LUMINOUS FLUX

138 - 168 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of CERVA 5 INGROUND.

Mounting position	**Floor Recessed**	Operating voltage	**24 V**
Housing	**Stainless steel / Aluminium**	Protection rating	**IP67**
Light source	**SMD LED**	Insulation class	**Class II**
Body dimensions	**Ø 50 × 90 mm**	Accessories	**HONEY COMB**
Control Gear	**Remote Electronic Driver**		

Markings and catalogue references **CE**

Options per version

Beams 15° (N), 24° (M), 36° (W) | Control On-Off

Luminous efficacy 46 - 56 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K	15°, 24°, 36°	3	**138**
930	3000 K	15°, 24°, 36°	3	**153**
940	4000 K	15°, 24°, 36°	3	**168**

Luminous flux range per version

Minimum 138 lm / 3 W / 927 / GR0408CL135ON

Maximum 168 lm / 3 W / 940 / GR0414CL135ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >