DECORUS

14 variants



Dimensions



Available colours

Dark Grey

DECORUS is a recessed LED ground luminaire made of aluminium. The body has a length of 400 mm, width of 145 mm and height of 150 mm. The recessed installation integrates the fitting into paving and landscape layouts. It provides a lighting point for nearby surfaces and features while keeping the body visually unobtrusive above ground. The optical surface is made of clear safety glass. The available 12°, 25°, 40° and 60° beams offer a choice from concentrated accent lighting to wider coverage. The 4000 K version has a colour rendering index of CRI80. The finish is dark grey. Control is available through On-Off and DMX512, to suit the lighting control requirements of the project. The construction is rated IP65 with an impact rating of IK10.

LUMINAIRE POWER

30 - 45 W

LUMINAIRE LUMINOUS FLUX

2,850 - 3,825 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of DECORUS.

Mounting position	**Floor Recessed**	Operating voltage	**230 V**
Housing	**Aluminium**	Protection rating	**IP65 / IK10**
Optic	**Safety Glass Clear**	Insulation class	**Class III**
Light source	**SMD LED**	Accessories	**ANTI-CONDENSATION KIT, JUNCTION BOX**
Body dimensions	**145 × 400 × 150 mm**		

Markings and catalogue references	**CE**

Options per version

Beams 12° (N), 25° (M), 40° (W), 60° (W) | Control On-Off, DMX512

Luminous efficacy 70 - 95 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
840	4000 K	12°, 25°, 40°, 60°	30 - 45	**2,850 - 3,825**

Luminous flux range per version

Minimum 2,850 lm / 30 W / 840 / GR0425CL103ON

Maximum 3,825 lm / 45 W / 840 / GR0435CL103DMX

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >