DENS D 60

6 variants



Dimensions



Available colours

White **Black** **Brown**

DENS D 60 is a surface-mounted LED ceiling luminaire made of aluminium. The body has a diameter of 600 mm and height of 65 mm. It mounts directly on the ceiling, leaving the body visible within the room. It suits homes, hospitality interiors and commercial spaces. The 3000 and 4000 K options with CRI80 allow the lighting to match the colour appearance required in the space. It is available in brown, black and white finishes. Control is available through TRIAC, to suit the lighting control requirements of the project. The construction is rated IP20 with an impact rating of IK05.

LUMINAIRE POWER

48 W

LUMINAIRE LUMINOUS FLUX

2,600 - 3,200 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of DENS D 60.

Mounting position	**Ceiling**	Body dimensions	**Ø 600 × 65 mm**
Housing	**Aluminium**	Operating voltage	**230 V**
Light source	**SMD LED**	Protection rating	**IP20 / IK05**

Markings and catalogue references	**CE**

Options per version

Control TRIAC

Luminous efficacy 54.2 - 66.7 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
830	3000 K		48	**2,600**
840	4000 K		48	**3,200**

Luminous flux range per version

Minimum 2,600 lm / 48 W / 830 / DEC0031CL010TR

Maximum 3,200 lm / 48 W / 840 / DEC0032CL010TR

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >