LENTE 3

4 variants



Dimensions



Available colours

White **Black**

LENTE 3 is a surface-mounted LED ceiling luminaire made of aluminium. The body has a diameter of 300 mm and height of 39 mm. It mounts directly on the ceiling, leaving the body visible within the room. It suits homes, hospitality interiors and commercial spaces. The 36° beam provides controlled coverage of the illuminated surface. The 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. It is available in black and white finishes. The construction is rated IP40 with an impact rating of IK04.

LUMINAIRE POWER

24 W

LUMINAIRE LUMINOUS FLUX

1,956 - 2,059 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of LENTE 3.

Mounting position	**Ceiling**	Control Gear	**Built-in ECG**
Housing	**Aluminium**	Operating voltage	**230 V**
Light source	**SMD LED**	Protection rating	**IP40 / IK04**
Body dimensions	**Ø 300 × 39 mm**		
Markings and catalogue references	**CE**		

Options per version

Beams 36° (W) | Control On-Off

Luminous efficacy 81.5 - 85.8 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	36°	24	**1,956**
940	4000 K	36°	24	**2,059**

Luminous flux range per version

Minimum 1,956 lm / 24 W / 930 / CM0723CL002ON

Maximum 2,059 lm / 24 W / 940 / CM0724CL002ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >