MAGNUM GAS

288 variants



Dimensions



MAGNUM GAS is an LED luminaire for commercial applications. It is offered in 354, 361 and 430 mm lengths, allowing the size to be selected for the application. The range includes surface-mounted, recessed and bracket-mounted versions. The installation method is selected to suit the supporting structure and the position of the fitting. It is offered with 60°, 90° and 120° beams, allowing the distribution to be selected for each application. The 3000, 4000, 5000 and 5700 K options with CRI70 allow the lighting to match the colour appearance required in the space. Control is available through On-Off and DALI2, to suit the lighting control requirements of the project.

LUMINAIRE POWER

80 - 150 W

LUMINAIRE LUMINOUS FLUX

12,540 - 23,250 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of MAGNUM GAS.

Mounting position	**Ceiling**	Insulation class	**Class I**
Light source	**SMD LED**		
Markings and catalogue references	**CE**		

Options per version

Beams 60° (W), 90° (VW), 120° (VW) | Control On-Off, DALI2

Luminous efficacy 147.3 - 165 lm/W | Length 354 - 430 mm | Width 330 - 400 mm | Height 76 - 160 mm

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
730	3000 K	60°, 90°, 120°	80 - 150	**12,540 - 22,088**
740	4000 K	60°, 90°, 120°	80 - 150	**13,200 - 23,250**
750	5000 K	60°, 90°, 120°	80 - 150	**13,200 - 23,250**
757	5700 K	60°, 90°, 120°	80 - 150	**13,200 - 23,250**

Luminous flux range per version

Minimum 12,540 lm / 80 W / 730 / CM0725ON

Maximum 23,250 lm / 150 W / 740 / CM0842ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >