
NIXOR 10 POOL

3 variants



Dimensions



Available colours

Inox

NIXOR 10 POOL is a recessed LED pool luminaire made of stainless steel and ABS. The body has a diameter of 110 mm and height of 32 mm. Recessing the luminaire into the wall integrates it into the pool structure. Positions and the number of fittings are selected to suit the shape and dimensions of the pool. The stainless steel and ABS body is combined with an IP68 protection rating. The optical surface is made of ABS. The wide 120° beam spreads light over a broader area. The 3000, 4000 and 6000 K options with CRI80 allow the lighting to match the colour appearance required in the space. The finish is stainless steel. The construction is rated IP68 with an impact rating of IK08.

LUMINAIRE POWER

6 W

LUMINAIRE LUMINOUS FLUX

700 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of NIXOR 10 POOL.

Mounting position	**Wall Recessed**	Body dimensions	**Ø 110 × 32 mm**
Housing	**Aluminium**	Control Gear	**Remote Electronic Driver**
Optic	**ABS**	Operating voltage	**12 V**
Light source	**SMD LED**	Protection rating	**IP68 / IK08**
Markings and catalogue references	**CE**		

Options per version

Beams 120° (VW) | Control On-Off

Luminous efficacy 116.7 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
830	3000 K	120°	6	**700**
840	4000 K	120°	6	**700**
860	6000 K	120°	6	**700**

Luminous flux range per version

Minimum 700 lm / 6 W / 830 / WF0657CL135ON

Maximum 700 lm / 6 W / 830 / WF0657CL135ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >