NON

24 variants



Dimensions



Available colours

White **Black**

NON is an LED spotlight for 48 V track made of aluminium. The body has a diameter of 30.5 mm and length of 111 mm. It forms part of a low-voltage track system, allowing lighting positions to follow the design. It suits homes, shops and hospitality spaces with different lighting requirements along the same track. The head offers vertical adjustment through 90° and horizontal adjustment through 360°. The available 12° and 55° beams offer a choice from concentrated accent lighting to wider coverage. The 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. It is available in black and white finishes. Control is available through On-Off and DALI2, with Casambi available in the corresponding version, to suit the lighting control requirements of the project. The construction is rated IP20.

LUMINAIRE POWER

7 W

LUMINAIRE LUMINOUS FLUX

538 - 595 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of NON.

Mounting position	**48V Track**	Control Gear	**Remote Electronic Driver**
Housing	**Aluminium**	Operating voltage	**48 V**
Light source	**SMD LED**	Protection rating	**IP20**
Body dimensions	**Ø 30.5 mm**		
Markings and catalogue references	**CE**		

Options per version

Beams 12° (N), 55° (W) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 76.9 - 85 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	12°, 55°	7	**538**
940	4000 K	12°, 55°	7	**595**

Luminous flux range per version

Minimum 538 lm / 7 W / 930 / LV0531CL002ON

Maximum 595 lm / 7 W / 940 / LV0533CL002ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >