PENDO 1 CEILING LED

12 variants



Dimensions



Available colours

White **Black** **Grey**

PENDO 1 CEILING LED is a surface-mounted LED ceiling luminaire made of aluminium. The body has a diameter of 120 mm and height of 140 mm. It mounts directly on the ceiling, leaving the body visible within the room. It suits homes, hospitality interiors and commercial spaces. The optical surface is made of clear safety glass. The wide 90° beam spreads light over a broader area. The 3000 and 4000 K options with CRI80 allow the lighting to match the colour appearance required in the space. It is available in black, white and grey finishes. Control is available through On-Off and DALI2, to suit the lighting control requirements of the project. The construction is rated IP20 with an impact rating of IK03.

LUMINAIRE POWER

11.6 W

LUMINAIRE LUMINOUS FLUX

1,020 - 1,070 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of PENDO 1 CEILING LED.

Mounting position	**Ceiling**	Body dimensions	**Ø 120 × 140 mm**
Housing	**Aluminium**	Control Gear	**Built-in ECG**
Optic	**Safety Glass Clear**	Protection rating	**IP20 / IK03**
Light source	**SMD LED**		
Markings and catalogue references	**CE**		

Options per version

Beams 90° (VW) | Control On-Off, DALI2

Luminous efficacy 87.9 - 92.2 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
830	3000 K	90°	11.6	**1,020**
840	4000 K	90°	11.6	**1,070**

Luminous flux range per version

Minimum 1,020 lm / 11.6 W / 830 / CM0869CL002ON

Maximum 1,070 lm / 11.6 W / 840 / CM0870CL002ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >