
PRODO 12

24 variants



Dimensions



Available colours

White **Black** **Grey** **Dark Grey**

PRODO 12 is an LED lighting bollard made of aluminium. Its ground-level placement helps organise lighting along paths, around planting and near entrances. It can be used individually or repeated to follow the layout of the outdoor space. The opal polycarbonate diffuser creates a luminous surface with a soft appearance. The 3000, 4000 and 6000 K options with CRI80 allow the lighting to match the colour appearance required in the space. It is available in dark grey, black, white and grey finishes. The construction is rated IP65 with an impact rating of IK08. The cylindrical body has a 120 mm diameter and is available in 250 mm and 810 mm heights, depending on the version.

LUMINAIRE POWER

12.5 W

LUMINAIRE LUMINOUS FLUX

765 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of PRODO 12.

Mounting position	**Bollard**	Operating voltage	**230 V**
Housing	**Aluminium**	Protection rating	**IP65 / IK08**
Optic	**Opal Polycarbonate**	Insulation class	**Class I**
Light source	**SMD LED**	Lighting direction	**Downwards**
Control Gear	**Built-in ECG**		

Markings and catalogue references	**CE**

Options per version

Beams 180° (VW) | Control On-Off

Luminous efficacy 61.2 lm/W | Height 250 - 810 mm | Diameter 120 mm

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
830	3000 K	180°	12.5	**765**
840	4000 K	180°	12.5	**765**
860	6000 K	180°	12.5	**765**

Luminous flux range per version

Minimum 765 lm / 12.5 W / 830 / BO0468CL103ON

Maximum 765 lm / 12.5 W / 830 / BO0468CL103ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >