PURE 230 CLEAR

70 variants



Dimensions



Available colours

Inox

PURE 230 CLEAR is a recessed LED ground luminaire made of aluminium and stainless steel. The body has a diameter of 234 mm and height of 196 mm. The recessed installation integrates the fitting into paving and landscape layouts. It provides a lighting point for nearby surfaces and features while keeping the body visually unobtrusive above ground. The head offers horizontal adjustment through 350°. The optical surface is made of clear safety glass. The available 5°–60° beams offer a choice from concentrated accent lighting to wider coverage. The 3000 K version has a colour rendering index of CRI80. The finish is stainless steel. Control is available through On-Off and DALI2, to suit the lighting control requirements of the project. The construction is rated IP68 with an impact rating of IK10.

LUMINAIRE POWER

14 - 36 W

LUMINAIRE LUMINOUS FLUX

1,190 - 2,592 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of PURE 230 CLEAR.

Mounting position	**Floor Recessed**	Control Gear	**Remote Electronic Driver**
Housing	**Aluminium, Stainless steel**	Colour uniformity	**3 SDCM**
Optic	**Safety Glass Clear**	Protection rating	**IP68 / IK10**
Light source	**SMD LED**	Insulation class	**Class III**
Body dimensions	**Ø 234 × 196 mm**		

Markings and catalogue references **CE**

Options per version

Beams 5° (UN), 8° (UN), 15° (N), 20° (N), 30° (M), 40° (W), 60° (W) | Control On-Off, DALI2

Luminous efficacy 72 - 85 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
830	3000 K	5°, 8°, 15°, 20°, 30°, 40°, 60°	14 - 36	**1,190 - 2,592**

Luminous flux range per version

Minimum 1,190 lm / 14 W / 830 / GR0442CL135ON

Maximum 2,592 lm / 36 W / 830 / GR0470CL135ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >