

PURE 80 DECUS

20 variants



Dimensions



Available colours

Black **Silver**

PURE 80 DECUS is a recessed LED ground luminaire made of aluminium. The body has a diameter of 126 mm and height of 93 mm. The recessed installation integrates the fitting into paving and landscape layouts. It provides a lighting point for nearby surfaces and features while keeping the body visually unobtrusive above ground. The optical surface is available with clear or sandblasted glass. The 2700, 3000, 3500, 4000 and 6500 K options with CRI90 allow the lighting to match the colour appearance required in the space. It is available in silver and black finishes. Control is available through On-Off and DALI2, to suit the lighting control requirements of the project. The construction is rated IP67 with an impact rating of IK06.

LUMINAIRE POWER

10 W

LUMINAIRE LUMINOUS FLUX

463 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of PURE 80 DECUS.

Mounting position	**Floor Recessed**	Control Gear	**Remote Electronic Driver**
Housing	**Aluminium**	Colour uniformity	**3 SDCM**
Optic	**Clear / Frosted glass**	Operating voltage	**24 V**
Light source	**SMD LED**	Protection rating	**IP67 / IK06**
Body dimensions	**Ø 126 × 93 mm**	Insulation class	**Class II**

Markings and catalogue references	**CE**

Options per version

Control On-Off, DALI2

Luminous efficacy 46.3 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K		10	**463**
930	3000 K		10	**463**
935	3500 K		10	**463**
940	4000 K		10	**463**
965	6500 K		10	**463**

Luminous flux range per version

Minimum 463 lm / 10 W / 930 / GR0512CL155ON

Maximum 463 lm / 10 W / 930 / GR0512CL155ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >