RAVUS WALL 10 M

4 variants



Dimensions



Available colours

White **Black**

RAVUS WALL 10 M is an LED wall luminaire made of aluminium. The body has a length of 240 mm, width of 130 mm and height of 32 mm. It adds a wall lighting point in homes, hotels and reception spaces. It complements the main lighting and draws attention to the area where it is installed. The 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. It is available in black and white finishes. The construction is rated IP20.

LUMINAIRE POWER

24 W

LUMINAIRE LUMINOUS FLUX

1,500 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of RAVUS WALL 10 M.

Mounting position	**Wall Mounted**	Body dimensions	**130 × 240 × 32 mm**
Housing	**Aluminium**	Operating voltage	**230 V**
Light source	**SMD LED**	Protection rating	**IP20**

Markings and catalogue references	**CE**

Options per version

Control On-Off

Luminous efficacy 62.5 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K		24	**1,500**
940	4000 K		24	**1,500**

Luminous flux range per version

Minimum 1,500 lm / 24 W / 930 / DEW0211CL002ON

Maximum 1,500 lm / 24 W / 930 / DEW0211CL002ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >