
RAVUS WALL 7S

2 variants



Dimensions



Available colours

White

RAVUS WALL 7S is an LED wall luminaire made of aluminium and acrylic. The body has a length of 450 mm, width of 100 mm and height of 40 mm. It adds a wall lighting point in homes, hotels and reception spaces. It complements the main lighting and draws attention to the area where it is installed. The 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. The finish is white. The construction is rated IP20 with an impact rating of IK03.

LUMINAIRE POWER

12 W

LUMINAIRE LUMINOUS FLUX

1,117 - 1,173 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of RAVUS WALL 7S.

Mounting position	**Wall Mounted**	Body dimensions	**100 × 450 × 40 mm**
Housing	**Aluminium**	Protection rating	**IP20 / IK03**
Light source	**SMD LED**		
Markings and catalogue references	**CE**		

Options per version

Control On-Off

Luminous efficacy 93.1 - 97.8 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K		12	**1,117**
940	4000 K		12	**1,173**

Luminous flux range per version

Minimum 1,117 lm / 12 W / 930 / DEW0221CL001ON

Maximum 1,173 lm / 12 W / 940 / DEW0222CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >