REGIO FLEX

12 variants



Dimensions



REGIO FLEX is a linear LED facade luminaire made of aluminium. The body has a length of 990 mm, width of 40 mm and height of 73 mm. Its elongated form allows lighting to follow facades, edges and architectural surfaces. The mounting position is chosen to suit the part of the building that needs emphasis. It can be installed on a wall, on the floor and on the ceiling, depending on the version and mounting arrangement. The available 5°–60° beams offer a choice from concentrated accent lighting to wider coverage. The 10x60° oval distribution provides elongated coverage for surfaces and routes with a matching geometry. The 3000 and 4000 K options with CRI80 allow the lighting to match the colour appearance required in the space. The construction is rated IP65 with an impact rating of IK05.

LUMINAIRE POWER

24 W

LUMINAIRE LUMINOUS FLUX

1,920 - 2,016 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of REGIO FLEX.

Mounting position	**Ceiling, Wall Mounted, Floor, Amenity**	Operating voltage	**24 V**
Housing	**Aluminium**	Protection rating	**IP65 / IK05**
Light source	**SMD LED**	Insulation class	**Class III**
Body dimensions	**40 × 990 × 73 mm**		

Options per version

Beams 5° (UN), 8° (UN), 10x60° (ASY), 15° (N), 30° (M), 60° (W)

Luminous efficacy 80 - 84 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
830	3000 K	5°, 8°, 10x60°, 15°, 30°, 60°	24	**1,920**
840	4000 K	5°, 8°, 10x60°, 15°, 30°, 60°	24	**2,016**

Luminous flux range per version

Minimum 1,920 lm / 24 W / 830 / FA4081

Maximum 2,016 lm / 24 W / 840 / FA4087

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >