
SEDO SQUARE SP

20 variants



Dimensions



SEDO SQUARE SP is a suspended LED luminaire with an acoustic frame and an aluminium body. The body has a length of 530 mm, width of 530 mm and height of 300 mm. The square form and acoustic frame become part of the ceiling composition. It suits work, meeting and hospitality spaces where lighting is combined with acoustic elements. The opal polycarbonate diffuser creates a luminous surface with a soft appearance. The wide 115° beam spreads light over a broader area. The 3000 and 4000 K options with CRI80 allow the lighting to match the colour appearance required in the space. Control is available through On-Off and DALI2, to suit the lighting control requirements of the project. The construction is rated IP20 with an impact rating of IK03.

LUMINAIRE POWER

15.6 - 51.9 W

LUMINAIRE LUMINOUS FLUX

1,440 - 4,000 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of SEDO SQUARE SP.

Mounting position	**Pendant**	Operating voltage	**230 V**
Housing	**Aluminium, Acoustic panel**	Protection rating	**IP20 / IK03**
Optic	**Opal Polycarbonate**	Insulation class	**Class I**
Light source	**SMD LED**	Accessories	**COLORED CABLES**
Body dimensions	**530 × 530 × 300 mm**		

Markings and catalogue references	**CE**

Options per version

Beams 115° (VW) | Control On-Off, DALI2

Luminous efficacy 74 - 97.3 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
830	3000 K	115°	15.6 - 51.9	**1,440 - 3,840**
840	4000 K	115°	15.6 - 51.9	**1,520 - 4,000**

Luminous flux range per version

Minimum 1,440 lm / 15.6 W / 830 / PRA0575ON

Maximum 4,000 lm / 51.9 W / 840 / PRA0584ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >