SICA S

6 variants



Dimensions



Available colours

White **Black**

SICA S is a surface-mounted LED ceiling luminaire made of aluminium. The body has a diameter of 40 mm and height of 154.5 mm. It mounts directly on the ceiling, leaving the body visible within the room. It suits homes, hospitality interiors and commercial spaces. The head offers vertical adjustment through 180° and horizontal adjustment through 360°. The 36° beam provides controlled coverage of the illuminated surface. The 2700, 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. It is available in black and white finishes. The construction is rated IP20 with an impact rating of IK02.

LUMINAIRE POWER

6 W

LUMINAIRE LUMINOUS FLUX

463 - 512 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of SICA S.

Mounting position	**Ceiling**	Control Gear	**Built-in ECG**
Housing	**Aluminium**	Operating voltage	**230 V**
Light source	**SMD LED**	Protection rating	**IP20 / IK02**
Body dimensions	**Ø 40 × 154.5 mm**	Accessories	**HONEY COMB**
Markings and catalogue references	**CE**		

Options per version

Beams 36° (W) | Control On-Off

Luminous efficacy 77.2 - 85.3 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K	36°	6	**463**
930	3000 K	36°	6	**488**
940	4000 K	36°	6	**512**

Luminous flux range per version

Minimum 463 lm / 6 W / 927 / CM0873CL002ON

Maximum 512 lm / 6 W / 940 / CM0875CL002ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >