
SISTO PANEL SQ

8 variants



Dimensions



Available colours

White **Grey**

SISTO PANEL SQ is a recessed LED panel made of an acoustic frame and aluminium. The body has a length of 605 mm, width of 605 mm and height of 40 mm. The flat construction integrates into the ceiling and suits workplaces, corridors and commercial interiors. The panel surface contributes to the overall lighting appearance of the space. The 30° beam concentrates light for accenting objects and individual features. The 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. It is available in white and grey finishes. Control is available through On-Off and DALI2, to suit the lighting control requirements of the project. The construction is rated IP20 with an impact rating of IK04.

LUMINAIRE POWER

32 W

LUMINAIRE LUMINOUS FLUX

3,648 - 3,840 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of SISTO PANEL SQ.

Mounting position	**Ceiling Recessed**	Control Gear	**Remote Electronic Driver**
Housing	**Acoustic panel, Aluminium**	Operating voltage	**230 V**
Light source	**SMD LED**	Protection rating	**IP20 / IK04**
Body dimensions	**605 × 605 × 40 mm**		
Markings and catalogue references	**CE**		

Options per version

Beams 30° (M) | Control On-Off, DALI2

Luminous efficacy 114 - 120 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	30°	32	**3,648**
940	4000 K	30°	32	**3,840**

Luminous flux range per version

Minimum 3,648 lm / 32 W / 930 / DL5669CL001ON

Maximum 3,840 lm / 32 W / 940 / DL5670CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >