
SOROR 2

96 variants



Dimensions



Available colours

White **Black** **Grey** **Anthracite**

SOROR 2 is an outdoor LED spotlight made of aluminium. The body has a length of 229 mm, width of 177 mm and height of 257 mm. It suits gardens, entrances and exterior surfaces that need accent lighting. The position of the spotlight determines which features of the landscape are highlighted. It can be installed on a wall, on the floor and on the ceiling, depending on the version and mounting arrangement. The optical construction combines clear safety glass and a Fresnel lens. The available 9°–60° beams offer a choice from concentrated accent lighting to wider coverage. The 4000 K version has a colour rendering index of CRI80. It is available in anthracite, black, white and grey finishes. Control is available through On-Off and DALI2, to suit the lighting control requirements of the project. The construction is rated IP67 with an impact rating of IK08.

LUMINAIRE POWER

40 - 45 W

LUMINAIRE LUMINOUS FLUX

2,960 - 3,330 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of SOROR 2.

Mounting position	**Ceiling, Wall Mounted, Floor**	Control Gear	**Built-in ECG**
Housing	**Aluminium**	Colour uniformity	**3 SDCM**
Optic	**Clear safety glass / Fresnel**	Operating voltage	**230 V**
Light source	**SMD LED**	Protection rating	**IP67 / IK08**
Body dimensions	**177 × 229 × 257 mm**	Insulation class	**Class I**

Markings and catalogue references	**CE**

Options per version

Beams 9° (UN), 14° (N), 20° (N), 30° (M), 40° (W), 60° (W) | Control On-Off, DALI2

Luminous efficacy 74 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
840	4000 K	9°, 14°, 20°, 30°, 40°, 60°	40 - 45	**2,960 - 3,330**

Luminous flux range per version

Minimum 2,960 lm / 40 W / 840 / PJ0613CL009ON

Maximum 3,330 lm / 45 W / 840 / PJ0619CL009ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >