SPOT HANDRAIL

10 variants



Dimensions



Available colours

Inox

SPOT HANDRAIL is a compact LED handrail luminaire made of stainless steel. The body has a diameter of 30 mm and height of 37.6 mm. The small lighting unit integrates into the handrail and brings light close to the route. It suits designs in which lighting forms part of the handrail construction itself. PMMA lenses shape the light leaving the LED unit. It is offered with 40° and 90° beams, allowing the distribution to be selected for each application. The 2200, 2700, 3000, 4000 and 6000 K options with CRI80 allow the lighting to match the colour appearance required in the space. The finish is stainless steel. The construction is rated IP65 with an impact rating of IK04.

LUMINAIRE POWER

1 W

LUMINAIRE LUMINOUS FLUX

90 - 110 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of SPOT HANDRAIL.

Mounting position	**Ceiling Recessed**	Body dimensions	**Ø 30 × 37.6 mm**
Housing	**Inox**	Control Gear	**Remote Electronic Driver**
Optic	**PMMA lenses**	Operating voltage	**230 V**
Light source	**SMD LED**	Protection rating	**IP65 / IK04**
Markings and catalogue references	**CE**		

Options per version

Beams 40° (W), 90° (VW) | Control On-Off

Luminous efficacy 90 - 110 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
822	2200 K	40°, 90°	1	**90**
827	2700 K	40°, 90°	1	**95**
830	3000 K	40°, 90°	1	**100**
840	4000 K	40°, 90°	1	**105**
860	6000 K	40°, 90°	1	**110**

Luminous flux range per version

Minimum 90 lm / 1 W / 822 / DL5671CL135ON

Maximum 110 lm / 1 W / 860 / DL5679CL135ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >