STRADALE MICRO L

160 variants



Dimensions



STRADALE MICRO L is an LED street luminaire. The body has a length of 530 mm, width of 250 mm and height of 81 mm. It is designed for pole mounting and the illumination of road surfaces. The available optical versions allow the distribution to be selected for the road geometry and arrangement of poles. The optical options are T2M53007, T2M55008, T2S53001, T2S55004, T3M53009, T3M55005, T3M55010, T3S53002, T3S53003 and T3S55006, allowing the version to be matched to the road lighting design. The 3000, 4000, 5000 and 5700 K options with CRI70 allow the lighting to match the colour appearance required in the space. Control is available through On-Off and DALI2, to suit the lighting control requirements of the project. The construction is rated IP66 with an impact rating of IK10.

LUMINAIRE POWER

120 - 150 W

LUMINAIRE LUMINOUS FLUX

14,820 - 21,000 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of STRADALE MICRO L.

Mounting position	**Pole Mounted**	Protection rating	**IP66 / IK10**
Light source	**SMD LED**	Insulation class	**Class II**
Body dimensions	**250 × 530 × 81 mm**		

Markings and catalogue references	**CE**

Options per version

Beams (II), (III) | Control On-Off, DALI2

Luminous efficacy 123.5 - 140 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
730	3000 K		120 - 150	**14,820 - 19,950**
740	4000 K		120 - 150	**15,600 - 21,000**
750	5000 K		120 - 150	**15,600 - 21,000**
757	5700 K		120 - 150	**15,600 - 21,000**

Luminous flux range per version

Minimum 14,820 lm / 120 W / 730 / ST0883ON

Maximum 21,000 lm / 150 W / 740 / ST0948ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >