
# UMBRA 4

**3 variants**



## Dimensions




## Available colours

**Grey**

UMBRA 4 features changeable CCT: 3000 / 4000 / 5700 K. Colour temperature is selected using the switch on the luminaire. It is available with On-Off control. Power, dimensions and other specifications are listed for each variant. The listed luminous flux corresponds to the 4000 K reference setting where documented.

**LUMINAIRE POWER**

30 - 70 W

**LUMINAIRE LUMINOUS FLUX**

3,750 - 8,750 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

**See all variants on bright.gr >**

# Technical characteristics

## Common data

Characteristics that apply to all versions of UMBRA 4.

| | | | |
|---|---|---|---|
| Mounting position | **Pole Mounted** | Body dimensions | **191 × 541 × 75 mm** |
| Housing | **Aluminium** | Protection rating | **IP65 / IK08** |
| Light source | **SMD LED** | | |
| **Markings and catalogue references** | **CE** | | |

## Options per version

### Control On-Off

Luminous efficacy 125 lm/W

### Luminous flux range per version

Minimum 3,750 lm / 30 W / AM0793CL003ON

Maximum 8,750 lm / 70 W / AM0795CL003ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

**See all variants on bright.gr** >