
VITIS 200

16 variants



Dimensions



Available colours

White **Black**

VITIS 200 is a linear LED luminaire made of aluminium. The body has a diameter of 208 mm and height of 208 mm. The linear form suits utility spaces, storage areas and circulation routes where lighting follows the length of the space. Repeated fittings can be arranged to cover larger areas. The optical surface is made of clear glass. It is offered with 30° and 60° beams, allowing the distribution to be selected for each application. The 3000 and 4000 K options with CRI90 allow the lighting to match the colour appearance required in the space. It is available in black and white finishes. Control is available through On-Off and DALI2, to suit the lighting control requirements of the project. The construction is rated IP20 with an impact rating of IK02.

LUMINAIRE POWER

60 W

LUMINAIRE LUMINOUS FLUX

4,991 - 5,254 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of VITIS 200.

Mounting position	**Ceiling**	Body dimensions	**Ø 208 × 208 mm**
Housing	**Aluminium**	Control Gear	**Built-in ECG**
Optic	**Clear Glass**	Operating voltage	**230 V**
Light source	**SMD LED**	Protection rating	**IP20 / IK02**
Markings and catalogue references	**CE**		

Options per version

Beams 30° (M), 60° (W) | Control On-Off, DALI2

Luminous efficacy 83.2 - 87.6 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	30°, 60°	60	**4,991**
940	4000 K	30°, 60°	60	**5,254**

Luminous flux range per version

Minimum 4,991 lm / 60 W / 930 / CM0883CL002ON

Maximum 5,254 lm / 60 W / 940 / CM0885CL002ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >