VELOX 5 Q

24 variants



Dimensions



Available colours

White **Black**

VELOX 5 Q is a track or ceiling spotlight with an aluminium body and 95 mm width, 50 mm height. It suits retail, residential, hospitality and display spaces where the light needs to be directed towards products, surfaces or points of interest. The asymmetric distribution directs light to one side, helping with walls, circulation areas, shelving or layouts where the light needs to work off-axis. With the right adapter, it can be used on single-phase or three-phase track; single-phase keeps the installation in one switching group, while three-phase allows different groups of spotlights to be controlled separately. It is available in white and black finishes, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects.

LUMINAIRE POWER

8.3 - 21.1 W

LUMINAIRE LUMINOUS FLUX

961 - 1,900 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of VELOX 5 Q.

Mounting position	**Track, Ceiling**
Housing	**Aluminium**
Light source	**COB LED**
Body dimensions	**95 × 95 × 50 mm**
Control Gear	**Built-in ECG**
Colour uniformity	**3 SDCM**
Ripple	**3**
Operating voltage	**230 V**

Power factor	**0.96**
Protection rating	**IP40 / IK02**
Insulation class	**Class II**
Lifetime	**>60.000h L80B10@35°C**
Operating temperature	**-10…+45°C**
Operating humidity	**5…95%**
Lighting direction	**Sideways**
Accessories	**BASE MAX 10.5, ANTI GLARE OPTION, ASYMMETRIC ANTI GLARE OPTION**

Markings and catalogue references	**CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams (ASY) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 89.1 - 125.1 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
935	3500 K		8.3 - 21.1	**961 - 1,880**
945	4500 K		8.3 - 21.1	**1,038 - 1,900**

Luminous flux range per version

Minimum 961 lm / 8.3 W / 935 / SP0127CL001ON

Maximum 1,900 lm / 21.1 W / 945 / SP0130CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >