
UBER 1 TR

210 variants



Dimensions



Available colours

White | Black | Grey | Gold | Copper

UBER 1 TR is a track or ceiling spotlight with an aluminium body and 120 mm diameter. It suits retail, residential, hospitality and display spaces where the light needs to be directed towards products, surfaces or points of interest. With the right adapter, it can be used on single-phase or three-phase track; single-phase keeps the installation in one switching group, while three-phase allows different groups of spotlights to be controlled separately. It is available in white, black, grey, gold and copper finishes, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects.

LUMINAIRE POWER

12.9 - 46.7 W

LUMINAIRE LUMINOUS FLUX

1,441 - 4,972 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of UBER 1 TR.

Mounting position	**Track, Ceiling**	Operating voltage	**230 V**
Housing	**Aluminium**	Power factor	**0.96**
Optic	**Lens**	Protection rating	**IP40 / IK04**
Light source	**COB LED**	Insulation class	**Class II**
Body dimensions	**Ø 120 × 100 mm**	Lifetime	**>60.000h L80B10@35°C**
Control Gear	**Built-in ECG**	Operating temperature	**-10…+45°C**
Colour uniformity	**3 SDCM**	Operating humidity	**5…95%**
Ripple	**3**	Lighting direction	**Sideways**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 60° (XW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 97.8 - 117.4 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	60°	12.9 - 46.7	**1,441 - 4,744**
940	4000 K	60°	12.9 - 46.7	**1,514 - 4,972**

Luminous flux range per version

Minimum 1,441 lm / 12.9 W / 930 / SP0723CL001ON

Maximum 4,972 lm / 46.7 W / 940 / SP0736CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >