SALUS 7 H

111 variants



Dimensions



Available colours

White **Black** **Grey**

SALUS 7 H is a track or ceiling spotlight for high-output LED and COIN 111 sources, with an aluminium body and 120 mm diameter. It suits retail, residential, hospitality and display spaces where the light needs to be directed towards products, surfaces or points of interest. The 8°–45° beam range allows the product to cover both focused accent lighting and wider illumination. The replaceable source gives flexibility in lamp selection and makes future maintenance or changes in lighting effect easier. It is available in white, black and grey finishes, with special RAL colours available on request for project-specific schemes.

LUMINAIRE POWER

7.8 - 11.7 W

LUMINAIRE LUMINOUS FLUX

916 - 1,359 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of SALUS 7 H.

Mounting position	**Track, Ceiling**	Protection rating	**IP20 / IK02**
Housing	**Aluminium**	Insulation class	**Class I**
Body dimensions	**Ø 120 × 50 mm**	Lifetime	**>60.000h L80B10@35°C**
Ripple	**3**	Operating temperature	**-10…+45°C**
Operating voltage	**230 V**	Operating humidity	**5…95%**
Power factor	**0.96**	Lighting direction	**Sideways**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 8° (UN), 25° (NM), 45° (W) | Control On-Off, DALI2, DALI2 + Casambi | Light source H.P. LED, COIN 111

Luminous efficacy 108.2 - 129.2 lm/W | UGR longwise / parallel 7 - 18 / 7 - 18

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	8°, 25°, 45°	7.8 - 11.7	**916 - 1,266**
940	4000 K	8°, 25°, 45°	7.8 - 11.7	**1,008 - 1,359**

Luminous flux range per version

Minimum 916 lm / 7.8 W / 930 / SP1554CL001ON

Maximum 1,359 lm / 11.7 W / 940 / SP1557CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >