TORRIS 3R ADTR A2 LED

630 variants



Dimensions



Available colours

White | Black | Grey | Chrome | Nickel

TORRIS 3R ADTR A2 LED is a track or ceiling spotlight with an aluminium body and 55 mm diameter. It suits retail, residential, hospitality and display spaces where the light needs to be directed towards products, surfaces or points of interest. The 17°–36° beam range allows the product to cover both focused accent lighting and wider illumination. With the right adapter, it can be used on single-phase or three-phase track; single-phase keeps the installation in one switching group, while three-phase allows different groups of spotlights to be controlled separately. Its anti-glare approach helps create a more comfortable lighting environment, especially in spaces where people spend longer periods of time. It is available in white, black, grey, chrome and nickel finishes, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects.

LUMINAIRE POWER

6 - 10.8 W

LUMINAIRE LUMINOUS FLUX

610 - 1,070 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of TORRIS 3R ADTR A2 LED.

Mounting position	**Track, Ceiling**	Power factor	**0.96**
Housing	**Aluminium**	Protection rating	**IP20 / IK04**
Optic	**Safety Glass Clear**	Insulation class	**Class II**
Light source	**COB LED**	Lifetime	**>60.000h L80B10@35°C**
Body dimensions	**Ø 55 × 150 mm**	Operating temperature	**-10…+45°C**
Ripple	**3**	Operating humidity	**5…95%**
Operating voltage	**230 V**	Lighting direction	**Sideways**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 17° (N), 24° (NM), 36° (M) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 93.9 - 107.3 lm/W | UGR longwise / parallel 20 - 25 / 20 - 25

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	17°, 24°, 36°	6 - 10.8	**610 - 1,014**
940	4000 K	17°, 24°, 36°	6 - 10.8	**644 - 1,070**

Luminous flux range per version

Minimum 610 lm / 6 W / 930 / SP1606CL001ON

Maximum 1,070 lm / 10.8 W / 940 / SP1619CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >