
# VENTUS 2P ADTR

**432 variants**



### Dimensions




### Available colours

**White** **Black** **Grey**

VENTUS 2P ADTR is a track or ceiling spotlight with an aluminium body and 145 mm width, 100 mm height. It suits retail, residential, hospitality and display spaces where the light needs to be directed towards products, surfaces or points of interest. The 15°–60° beam range allows the product to cover both focused accent lighting and wider illumination. With the right adapter, it can be used on single-phase or three-phase track; single-phase keeps the installation in one switching group, while three-phase allows different groups of spotlights to be controlled separately. It is available in white, black and grey finishes, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects.

**LUMINAIRE POWER**

## 12.8 - 40.4 W

**LUMINAIRE LUMINOUS FLUX**

## 1,458 - 4,484 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

**See all variants on bright.gr >**

# Technical characteristics

## Common data

Characteristics that apply to all versions of VENTUS 2P ADTR.

| | |
|---|---|
| Mounting position | **Track, Ceiling** |
| Housing | **Aluminium** |
| Optic | **Clear Polycarbonate** |
| Light source | **COB LED** |
| Body dimensions | **145 × 145 × 100 mm** |
| Control Gear | **Built-in ECG** |
| Colour uniformity | **3 SDCM** |
| Ripple | **3** |
| Operating voltage | **230 V** |

| | |
|---|---|
| Power factor | **0.96** |
| Protection rating | **IP20 / IK07** |
| Insulation class | **Class II** |
| Lifetime | **>60.000h L80B10@35°C** |
| Operating temperature | **-10…+45°C** |
| Operating humidity | **5…95%** |
| Lighting direction | **Sideways** |
| Accessories | **SHADER111, WALL WASHER, RGB CONTROLLER** |

| | |
|---|---|
| **Markings and catalogue references** | **CE • LM80 • LM79 • TM21 • REACH** |

## Options per version

**Beams 15° (N), 24° (NM), 40° (W), 60° (XW) | Control On-Off, DALI2, DALI2 + Casambi**

Luminous efficacy 99 - 119.7 lm/W

| CRI/CCT | Colour temperature | Beams | Power (W) | Luminous flux (lm) |
|---|---|---|---|---|
| **930** | 3000 K | 15°, 24°, 40°, 60° | 12.8 - 40.4 | **1,458 - 4,279** |
| **940** | 4000 K | 15°, 24°, 40°, 60° | 12.8 - 40.4 | **1,532 - 4,484** |

### Luminous flux range per version

Minimum 1,458 lm / 12.8 W / 930 / SP1653CL001ON

Maximum 4,484 lm / 40.4 W / 940 / SP1664CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

**See all variants on bright.gr >**