ARCUS PENDO 3 H.P.LED

108 variants



Dimensions



Available colours

White Black Grey

ARCUS PENDO 3 H.P.LED is a track or ceiling spotlight with an aluminium body and 120 mm diameter. It suits retail, residential, hospitality and display spaces where the light needs to be directed towards products, surfaces or points of interest. The 8°–45° beam range allows the product to cover both focused accent lighting and wider illumination. With the right adapter, it can be used on single-phase or three-phase track; single-phase keeps the installation in one switching group, while three-phase allows different groups of spotlights to be controlled separately. Low glare combined with CRI90 makes it suitable for projects with high visual-comfort requirements, including offices, hospitality spaces and WELL or LEED-oriented applications. It is available in white, black and grey finishes, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects.

LUMINAIRE POWER

7.7 - 11.6 W

LUMINAIRE LUMINOUS FLUX

776 - 1,150 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of ARCUS PENDO 3 H.P.LED.

Mounting position	**Track, Ceiling**	Protection rating	**IP20 / IK02**
Housing	**Aluminium**	Insulation class	**Class II**
Light source	**H.P. LED**	Lifetime	**>60.000h L80B10@35°C**
Body dimensions	**Ø 120 × 65 mm**	Operating temperature	**-10…+45°C**
Ripple	**3**	Operating humidity	**5…95%**
Operating voltage	**230 V**	Lighting direction	**Sideways**
Power factor	**0.96**		

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 8° (UN), 25° (NM), 45° (W) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 92.3 - 111 lm/W | UGR longwise / parallel 8 - 19 / 8 - 19

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	8°, 25°, 45°	7.7 - 11.6	**776 - 1,071**
940	4000 K	8°, 25°, 45°	7.7 - 11.6	**855 - 1,150**

Luminous flux range per version

Minimum 776 lm / 7.7 W / 930 / SP1701CL001ON

Maximum 1,150 lm / 11.6 W / 940 / SP1704CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >