LEGATUS CAVUS 2

24 variants



Dimensions



Available colours

White **Black** **Grey** **Gold**

LEGATUS CAVUS 2 is a 48V spotlight with an aluminium body and 60 mm width, 40 mm height. It suits retail, residential, hospitality and display spaces where the light needs to be directed towards products, surfaces or points of interest. Low glare combined with CRI90 makes it suitable for projects with high visual-comfort requirements, including offices, hospitality spaces and WELL or LEED-oriented applications. It is available in white, black, grey and gold finishes, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects.

LUMINAIRE POWER

24 W

LUMINAIRE LUMINOUS FLUX

2,330 - 2,480 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of LEGATUS CAVUS 2.

Mounting position	**48V Track**	Power factor	**0.96**
Housing	**Aluminium**	Protection rating	**IP20 / IK02**
Optic	**PMMA**	Insulation class	**Class III**
Light source	**Linear LED**	Lifetime	**>50.000h L70B10@35°C**
Body dimensions	**60 × 1530 × 40 mm**	Operating temperature	**-10…+45°C**
Control Gear	**Built-in ECG**	Operating humidity	**5…95%**
Colour uniformity	**3 SDCM**	Lighting direction	**Sideways**
Ripple	**3**	Accessories	**LEGATUS CAVUS 2 TUBO COVER**
Operating voltage	**48 V**		

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 125° (VW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 97.1 - 103.3 lm/W | UGR longwise / parallel 18 / 8 - 9

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	125°	24	**2,330**
940	4000 K	125°	24	**2,480**

Luminous flux range per version

Minimum 2,330 lm / 24 W / 930 / LV0263CL001ON

Maximum 2,480 lm / 24 W / 940 / LV0264CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >