
LEGATUS VISO 2

72 variants



Dimensions



Available colours

White Black Grey Gold

LEGATUS VISO 2 is a 48V spotlight with a brass body and 20 mm diameter. It suits retail, residential, hospitality and display spaces where the light needs to be directed towards products, surfaces or points of interest. Low glare combined with CRI90 makes it suitable for projects with high visual-comfort requirements, including offices, hospitality spaces and WELL or LEED-oriented applications. It is available in white, black, grey and gold finishes, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects.

LUMINAIRE POWER

1.8 - 2.7 W

LUMINAIRE LUMINOUS FLUX

59 - 90 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of LEGATUS VISO 2.

Mounting position	**48V Track**	Operating voltage	**48 V**
Housing	**Brass**	Power factor	**0.96**
Optic	**Reflector**	Protection rating	**IP40 / IK07**
Light source	**H.P. LED**	Insulation class	**Class III**
Body dimensions	**Ø 20 × 190 mm**	Lifetime	**>50.000h L70B10@35°C**
Control Gear	**Built-in ECG**	Operating temperature	**-10…+45°C**
Colour uniformity	**3 SDCM**	Operating humidity	**5…95%**
Ripple	**3**	Lighting direction	**Sideways**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 360° (VW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 29.8 - 37.8 lm/W | UGR longwise / parallel 13 - 15 / 13 - 15

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K	360°	1.8 - 2.7	**59 - 81**
930	3000 K	360°	1.8 - 2.7	**61 - 83**
940	4000 K	360°	1.8 - 2.7	**68 - 90**

Luminous flux range per version

Minimum 59 lm / 1.8 W / 927 / LV0265CL001ON

Maximum 90 lm / 2.7 W / 940 / LV0270CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >