LEGATUS 35 SHADE

54 variants



Dimensions



Available colours

White **Black** **Grey**

LEGATUS 35 SHADE is a 48V spotlight with an aluminium body and 155 mm diameter. It suits retail, residential, hospitality and display spaces where the light needs to be directed towards products, surfaces or points of interest. The 20°–60° beam range allows the product to cover both focused accent lighting and wider illumination. It is available in white, black and grey finishes, with special RAL colours available on request for project-specific schemes.

LUMINAIRE POWER

2.4 - 6.2 W

LUMINAIRE LUMINOUS FLUX

225 - 613 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of LEGATUS 35 SHADE.

Mounting position	**48V Track**	Power factor	**0.96**
Housing	**Aluminium**	Protection rating	**IP20 / IK05**
Light source	**Linear LED**	Insulation class	**Class III**
Body dimensions	**Ø 155 × 55 mm**	Lifetime	**>50.000h L80B10@35°C**
Control Gear	**Built-in ECG**	Operating temperature	**-10…+45°C**
Colour uniformity	**3 SDCM**	Operating humidity	**5…95%**
Ripple	**3**	Lighting direction	**Sideways**
Operating voltage	**48 V**		

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 20° (NM), 40° (W), 60° (XW)

Luminous efficacy 93.3 - 98.9 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	20°, 40°, 60°	2.4 - 6.2	**225 - 585**
940	4000 K	20°, 40°, 60°	2.4 - 6.2	**235 - 613**

Luminous flux range per version

Minimum 225 lm / 2.4 W / 930 / LV0277CL001

Maximum 613 lm / 6.2 W / 940 / LV0282CL001

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >