
BENE 5F TRIMLESS ASYMMETRIC

108 variants



Dimensions



Available colours

White **Black** **Grey**

BENE 5F TRIMLESS ASYMMETRIC is a recessed ceiling luminaire with an aluminium body. It suits homes, offices, hotels and commercial spaces where the ceiling needs to remain clean and the lighting should integrate quietly into the architecture. As a larger version of the series, it provides increased light quantity and a stronger presence, while remaining easy to combine with smaller versions of the same family in one project. The asymmetric distribution directs light to one side, helping with walls, circulation areas, shelving or layouts where the light needs to work off-axis. It is available in white, black and grey finishes, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects. The recessed installation keeps the ceiling clean and allows the luminaire to work without drawing excessive attention.

LUMINAIRE POWER

6.1 - 12.8 W

LUMINAIRE LUMINOUS FLUX

252 - 534 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of BENE 5F TRIMLESS ASYMMETRIC.

Mounting position	**Ceiling Recessed**	Operating voltage	**15 V**
Housing	**Aluminium**	Power factor	**0.96**
Optic	**PMMA**	Protection rating	**IP20 / IK04**
Light source	**COB LED**	Insulation class	**Class III**
Body dimensions	**37 × 140 × 54 mm**	Lifetime	**>60.000h L80B10@35°C**
Control Gear	**Remote Electronic Driver**	Operating temperature	**-10…+45°C**
Colour uniformity	**3 SDCM**	Operating humidity	**5…95%**
Ripple	**3**	Lighting direction	**Sideways**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams - (ASY) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 36.5 - 47.2 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K	-	6.1 - 12.8	**252 - 467**
930	3000 K	-	6.1 - 12.8	**276 - 512**
935	3500 K	-	6.1 - 12.8	**282 - 523**
940	4000 K	-	6.1 - 12.8	**288 - 534**

Luminous flux range per version

Minimum 252 lm / 6.1 W / 927 / DL0205CL001ON

Maximum 534 lm / 12.8 W / 940 / DL0213CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >