SPOT BENE ROUND XL

18 variants



Dimensions



Available colours

White

SPOT BENE ROUND XL is a recessed ceiling luminaire with an aluminium body and 218 mm diameter. It suits homes, offices, hotels and commercial spaces where the ceiling needs to remain clean and the lighting should integrate quietly into the architecture. As the smaller version of the series, it suits areas that need a lighter visual presence without changing the design approach. The deep anti-glare optical system reduces the visibility of the light source and helps keep the light comfortable in everyday use. CRI90 supports faithful colour rendering. The optical distribution and glare performance should be assessed for the selected variant and the lighting design of the space. Special RAL colours can be requested for projects with a specific colour scheme. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects. The recessed installation keeps the ceiling clean and allows the luminaire to work without drawing excessive attention.

LUMINAIRE POWER

38 W

LUMINAIRE LUMINOUS FLUX

3,100 - 3,500 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of SPOT BENE ROUND XL.

Mounting position	**Ceiling Recessed**	Ripple	**3**
Housing	**Aluminium**	Power factor	**0.96**
Optic	**PMMA**	Protection rating	**IP40 / IK04**
Light source	**COB LED**	Operating temperature	**-10…+45°C**
Body dimensions	**Ø 218 × 100 mm**	Operating humidity	**5…95%**
Control Gear	**Remote Electronic Driver**	Lighting direction	**Downwards**
Colour uniformity	**3 SDCM**		

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 24° (NM), 48° (W) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 81.6 - 92.1 lm/W | UGR longwise / parallel 8 - 15 / 8 - 15

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	24°, 48°	38	**3,100**
935	3500 K	24°, 48°	38	**3,300**
940	4000 K	24°, 48°	38	**3,500**

Luminous flux range per version

Minimum 3,100 lm / 38 W / 930 / DL0227CL001ON

Maximum 3,500 lm / 38 W / 940 / DL0229CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >