
STELLA 3 LED

1,260 variants



Dimensions



Available colours

White **Black** **Grey** **Gold**

It suits homes, offices, hotels and commercial spaces where the ceiling needs to remain clean and the lighting should integrate quietly into the architecture. The standard 18°–60° beams allow a choice between narrower and wider lighting, depending on the application. Where coverage needs to extend along one axis, the oval 25x60° beam adds a useful option for elongated surfaces and circulation zones. Low glare combined with CRI90 makes it suitable for projects with high visual-comfort requirements, including offices, hospitality spaces and WELL or LEED-oriented applications. It is available in white, black, grey and gold finishes, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects. The recessed installation keeps the ceiling clean and allows the luminaire to work without drawing excessive attention. Body dimensions: Ø93×150 mm. The corresponding dimensions are listed for each variant.

LUMINAIRE POWER

6 - 10.8 W

LUMINAIRE LUMINOUS FLUX

572 - 1,004 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of STELLA 3 LED.

Mounting position	**Ceiling Recessed**	Protection rating	**IP40 / IK05**
Housing	**Aluminium**	Insulation class	**Class III**
Light source	**COB LED**	Lifetime	**>60.000h L80B10@35°C**
Body dimensions	**Ø 93 × 150 mm**	Operating temperature	**-10…+45°C**
Ripple	**3**	Operating humidity	**5…95%**
Power factor	**0.96**	Lighting direction	**Downwards**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams - (ASY), 18° (N), 24° (NM), 36° (M), 60° (XW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 87.3 - 100.7 lm/W | UGR longwise / parallel 16 - 27 / 16 - 27

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	-, 18°, 24°, 36°, 60°	6 - 10.8	**572 - 951**
935	3500 K	-, 18°, 24°, 36°, 60°	6 - 10.8	**588 - 977**
940	4000 K	-, 18°, 24°, 36°, 60°	6 - 10.8	**604 - 1,004**

Luminous flux range per version

Minimum 572 lm / 6 W / 930 / DL0701CL001ON

Maximum 1,004 lm / 10.8 W / 940 / DL0714CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >