ARTUS 4 SQUARE LED

567 variants



Dimensions



Available colours

White | Black | Grey

ARTUS 4 SQUARE LED is a recessed ceiling luminaire with an aluminium body. It suits homes, offices, hotels and commercial spaces where the ceiling needs to remain clean and the lighting should integrate quietly into the architecture. It is available in white, black and grey finishes, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects. The recessed installation keeps the ceiling clean and allows the luminaire to work without drawing excessive attention. Body dimensions: 85×85×127 mm. The corresponding dimensions are listed for each variant.

LUMINAIRE POWER

6 - 10.8 W

LUMINAIRE LUMINOUS FLUX

648 - 1,137 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of ARTUS 4 SQUARE LED.

Mounting position	**Ceiling Recessed**	Protection rating	**IP20 / IK05**
Housing	**Aluminium**	Insulation class	**Class III**
Light source	**COB LED**	Lifetime	**>60.000h L80B10@35°C**
Body dimensions	**85 × 85 × 127 mm**	Operating temperature	**-10…+45°C**
Control Gear	**Remote Electronic Driver**	Operating humidity	**5…95%**
Ripple	**3**	Lighting direction	**Downwards**
Operating voltage	**34.6 V**	Accessories	**ELECTRONIC TRANSFORMER**
Power factor	**0.96**		

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 18° (N), 24° (NM), 36° (M) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 99.8 - 114 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	18°, 24°, 36°	6 - 10.8	**648 - 1,078**
935	3500 K	18°, 24°, 36°	6 - 10.8	**666 - 1,108**
940	4000 K	18°, 24°, 36°	6 - 10.8	**684 - 1,137**

Luminous flux range per version

Minimum 648 lm / 6 W / 930 / DL1686CL001ON

Maximum 1,137 lm / 10.8 W / 940 / DL1699CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >