CERAM 4S H.P.LED

24 variants



Dimensions



Available colours

White

CERAM 4S H.P.LED is a recessed ceiling luminaire with an aluminium body. It suits homes, offices, hotels and commercial spaces where the ceiling needs to remain clean and the lighting should integrate quietly into the architecture. Special RAL colours can be requested for projects with a specific colour scheme. The recessed installation keeps the ceiling clean and allows the luminaire to work without drawing excessive attention.

LUMINAIRE POWER

3.3 - 4.9 W

LUMINAIRE LUMINOUS FLUX

310 - 479 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of CERAM 4S H.P.LED.

Mounting position	**Ceiling Recessed**	Power factor	**0.96**
Housing	**Γύψος, Αλουμίνιο**	Protection rating	**IP20 / IK02**
Light source	**H.P. LED**	Operating temperature	**-10…+45°C**
Body dimensions	**133 × 133 × 50 mm**	Operating humidity	**5…95%**
Ripple	**3**	Lighting direction	**Sideways**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 8° (UN), 25° (NM), 45° (W)

Luminous efficacy 90 - 104.2 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K	8°, 25°, 45°	3.3 - 4.9	**310 - 441**
930	3000 K	8°, 25°, 45°	3.3 - 4.9	**325 - 456**
935	3500 K	8°, 25°, 45°	3.3 - 4.9	**334 - 467**
940	4000 K	8°, 25°, 45°	3.3 - 4.9	**344 - 479**

Luminous flux range per version

Minimum 310 lm / 3.3 W / 927 / DL2504CL001

Maximum 479 lm / 4.9 W / 940 / DL2509CL001

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >