
FIXUS LED

1,890 variants



Dimensions



Available colours

White | Black | Grey | Gold | Chrome | Nickel

FIXUS LED is a recessed ceiling luminaire with an aluminium body and 73 mm diameter. It suits homes, offices, hotels and commercial spaces where the ceiling needs to remain clean and the lighting should integrate quietly into the architecture. Depending on the project, the 18°–60° beams can be used for either more concentrated or more open lighting. The oval option 25x60° complements the range when the light needs to follow a shelf, counter, corridor or long architectural line. Low glare combined with CRI90 makes it suitable for projects with high visual-comfort requirements, including offices, hospitality spaces and WELL or LEED-oriented applications. It is available in multiple finish options, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects. The recessed installation keeps the ceiling clean and allows the luminaire to work without drawing excessive attention.

LUMINAIRE POWER

6 - 10.8 W

LUMINAIRE LUMINOUS FLUX

684 - 1,335 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of FIXUS LED.

Mounting position	**Ceiling Recessed**	Power factor	**0.96**
Housing	**Aluminium**	Protection rating	**IP20 / IK05**
Optic	**Safety Glass Clear**	Insulation class	**Class III**
Light source	**COB LED**	Lifetime	**>60.000h L80B10@35°C**
Body dimensions	**Ø 73 × 75 mm**	Operating temperature	**-10…+45°C**
Control Gear	**Remote Electronic Driver**	Operating humidity	**5…95%**
Ripple	**3**	Lighting direction	**Downwards**
Operating voltage	**34.6 V**		

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams - (ASY), 18° (N), 24° (NM), 36° (M), 60° (XW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 104.6 - 133.7 lm/W | UGR longwise / parallel 17 - 28 / 17 - 28

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	-, 18°, 24°, 36°, 60°	6 - 10.8	**802 - 1,335**
935	3500 K	-, 18°, 24°, 36°, 60°	6 - 10.8	**743 - 1,236**
940	4000 K	-, 18°, 24°, 36°, 60°	6 - 10.8	**684 - 1,137**

Luminous flux range per version

Minimum 684 lm / 6 W / 940 / DL2734CL001ON

Maximum 1,335 lm / 10.8 W / 930 / DL2733CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >