STATUR SMALL 24

135 variants



Dimensions



Available colours

White **Black** **Grey**

STATUR SMALL 24 is a recessed ceiling luminaire with an integrated LED source, with an aluminium body and 240 mm diameter. It suits homes, offices, hotels and commercial spaces where the ceiling needs to remain clean and the lighting should integrate quietly into the architecture. The integrated LED source with CRI90 supports good colour rendering, with 16.2–26.3W versions, in 3000K and 4000K colour temperatures. It is available in white, black and grey finishes, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects. The recessed installation keeps the ceiling clean and allows the luminaire to work without drawing excessive attention. Suitable for recessed installation in outdoor ceilings, with IP54 protection.

LUMINAIRE POWER

16.2 - 26.3 W

LUMINAIRE LUMINOUS FLUX

1,713 - 2,677 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of STATUR SMALL 24.

Mounting position	**Ceiling Recessed**	Power factor	**0.96**
Housing	**Aluminium**	Protection rating	**IP54 / IK04**
Optic	**PMMA**	Insulation class	**Class III**
Light source	**SMD LED**	Lifetime	**>50.000h L80B10@35°C**
Body dimensions	**Ø 240 × 44 mm**	Operating temperature	**-10…+45°C**
Control Gear	**Remote Electronic Driver**	Operating humidity	**5…95%**
Colour uniformity	**3 SDCM**	Lighting direction	**Downwards**
Ripple	**3**	Accessories	**—**
Operating voltage	**36.2 V**		

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 118° (VW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 97.3 - 113 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	118°	16.2 - 26.3	**1,713 - 2,560**
935	3500 K	118°	16.2 - 26.3	**1,772 - 2,618**
940	4000 K	118°	16.2 - 26.3	**1,830 - 2,677**

Luminous flux range per version

Minimum 1,713 lm / 16.2 W / 930 / DL2850CL001ON

Maximum 2,677 lm / 26.3 W / 940 / DL2859CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >