
VIGOR IN M

9 variants



Dimensions



Available colours

White

VIGOR IN M is a recessed ceiling luminaire with an integrated LED source, with an aluminium body and 140 mm diameter. It suits homes, offices, hotels and commercial spaces where the ceiling needs to remain clean and the lighting should integrate quietly into the architecture. As the medium version of the series, it offers more presence than the smaller versions without becoming visually heavy. The integrated LED source with CRI90 supports good colour rendering, in 3000K and 4000K colour temperatures. Special RAL colours can be requested for projects with a specific colour scheme. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects. The recessed installation keeps the ceiling clean and allows the luminaire to work without drawing excessive attention.

LUMINAIRE POWER

10 W

LUMINAIRE LUMINOUS FLUX

850 - 900 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of VIGOR IN M.

Mounting position	**Ceiling Recessed**	Operating voltage	**230 V**
Housing	**Aluminium**	Power factor	**0.96**
Optic	**PMMA**	Protection rating	**IP20 / IK04**
Light source	**SMD LED**	Insulation class	**Class II**
Body dimensions	**Ø 140 × 28 mm**	Lifetime	**20.000h**
Control Gear	**Remote Electronic Driver**	Operating temperature	**-10…+45°C**
Colour uniformity	**3 SDCM**	Operating humidity	**5…95%**
Ripple	**3**	Lighting direction	**Downwards**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 115° (VW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 85 - 90 lm/W | UGR longwise / parallel 29 / 29

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	115°	10	**850**
935	3500 K	115°	10	**875**
940	4000 K	115°	10	**900**

Luminous flux range per version

Minimum 850 lm / 10 W / 930 / DL2860CL001ON

Maximum 900 lm / 10 W / 940 / DL2861CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >