STATUS 3F H.P.LED

162 variants



Dimensions



Available colours

White **Black** **Grey**

STATUS 3F H.P.LED is a recessed ceiling luminaire with an aluminium body and 157 mm width, 95 mm height, 467 mm length. It suits homes, offices, hotels and commercial spaces where the ceiling needs to remain clean and the lighting should integrate quietly into the architecture. Its medium scale offers more light quantity and a larger body than the simpler versions, while keeping a related appearance within the series. Low glare combined with CRI90 makes it suitable for projects with high visual-comfort requirements, including offices, hospitality spaces and WELL or LEED-oriented applications. It is available in white, black and grey finishes, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects. The recessed installation keeps the ceiling clean and allows the luminaire to work without drawing excessive attention.

LUMINAIRE POWER

23.3 - 35 W

LUMINAIRE LUMINOUS FLUX

2,325 - 3,448 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of STATUS 3F H.P.LED.

Mounting position	**Ceiling Recessed**	Operating voltage	**3x21 V**
Housing	**Μέταλλο, Αλουμίνιο**	Power factor	**0.96**
Optic	**Clear Polycarbonate**	Protection rating	**IP20 / IK07**
Light source	**H.P. LED**	Insulation class	**Class III**
Body dimensions	**157 × 467 × 95 mm**	Lifetime	**>60.000h L80B10@35°C**
Control Gear	**Remote Electronic Driver**	Operating temperature	**-10…+45°C**
Colour uniformity	**3 SDCM**	Operating humidity	**5…95%**
Ripple	**3**	Lighting direction	**Sideways**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 8° (UN), 25° (NM), 45° (W) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 91.7 - 110 lm/W | UGR longwise / parallel 3 - 14 / 4 - 14

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	8°, 25°, 45°	23.3 - 35	**2,325 - 3,211**
935	3500 K	8°, 25°, 45°	23.3 - 35	**2,443 - 3,330**
940	4000 K	8°, 25°, 45°	23.3 - 35	**2,562 - 3,448**

Luminous flux range per version

Minimum 2,325 lm / 23.3 W / 930 / DL3125CL001ON

Maximum 3,448 lm / 35 W / 940 / DL3128CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >