
STATUS S 3F LED

945 variants



Dimensions



Available colours

White **Black** **Grey**

STATUS S 3F LED is a recessed ceiling luminaire with an aluminium body and 97 mm width, 110 mm height, 283 mm length. It suits homes, offices, hotels and commercial spaces where the ceiling needs to remain clean and the lighting should integrate quietly into the architecture. The available 18°–60° beams cover everything from focused accent lighting to wider illumination. As an additional optical option, the oval 25x60° beam helps corridors, shelves, counters or elongated surfaces where the light needs to spread further along one axis. Its medium scale offers more light quantity and a larger body than the simpler versions, while keeping a related appearance within the series. As the smaller version of the series, it suits areas that need a lighter visual presence without changing the design approach. Low glare combined with CRI90 makes it suitable for projects with high visual-comfort requirements, including offices, hospitality spaces and WELL or LEED-oriented applications. It is available in white, black and grey finishes, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects. The recessed installation keeps the ceiling clean and allows the luminaire to work without drawing excessive attention.

LUMINAIRE POWER

18 - 32.4 W

LUMINAIRE LUMINOUS FLUX

1,944 - 3,411 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of STATUS S 3F LED.

Mounting position	**Ceiling Recessed**	Power factor	**0.96**
Housing	**Μέταλλο, Αλουμίνιο**	Protection rating	**IP20 / IK05**
Light source	**COB LED**	Operating temperature	**-10…+45°C**
Body dimensions	**97 × 283 × 110 mm**	Operating humidity	**5…95%**
Ripple	**3**	Lighting direction	**Sideways**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams - (ASY), 18° (N), 24° (NM), 36° (M), 60° (XW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 99.8 - 114 lm/W | UGR longwise / parallel 14 - 19 / 14 - 25

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	-, 18°, 24°, 36°, 60°	18 - 32.4	**1,944 - 3,234**
935	3500 K	-, 18°, 24°, 36°, 60°	18 - 32.4	**1,998 - 3,323**
940	4000 K	-, 18°, 24°, 36°, 60°	18 - 32.4	**2,052 - 3,411**

Luminous flux range per version

Minimum 1,944 lm / 18 W / 930 / DL3349CL001ON

Maximum 3,411 lm / 32.4 W / 940 / DL3362CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >