

MINI TALUS 1F LED

1,575 variants



Dimensions



Available colours

White | Black | Grey | Chrome | Nickel

MINI TALUS 1F LED is a recessed ceiling luminaire with a metal body and 125 mm width, 145 mm height, 125 mm length. It suits homes, offices, hotels and commercial spaces where the ceiling needs to remain clean and the lighting should integrate quietly into the architecture. Depending on the project, the 18°–60° beams can be used for either more concentrated or more open lighting. The oval option 25x60° complements the range when the light needs to follow a shelf, counter, corridor or long architectural line. As the smaller version of the series, it keeps a lighter presence and can be combined with larger versions when different light levels are needed within the same project. It is available in white, black, grey, nickel and chrome finishes, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects. The recessed installation keeps the ceiling clean and allows the luminaire to work without drawing excessive attention.

LUMINAIRE POWER

6 - 10.8 W

LUMINAIRE LUMINOUS FLUX

648 - 1,137 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of MINI TALUS 1F LED.

Mounting position	**Ceiling Recessed**	Protection rating	**IP20 / IK05**
Housing	**Metal**	Insulation class	**Class III**
Light source	**COB LED**	Lifetime	**>60.000h L80B10@35°C**
Body dimensions	**125 × 125 × 145 mm**	Operating temperature	**-10…+45°C**
Ripple	**3**	Operating humidity	**5…95%**
Operating voltage	**34.6 V**	Lighting direction	**Sideways**
Power factor	**0.96**		

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams - (ASY), 18° (N), 24° (NM), 36° (M), 60° (XW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 99.8 - 114 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	-, 18°, 24°, 36°, 60°	6 - 10.8	**648 - 1,078**
935	3500 K	-, 18°, 24°, 36°, 60°	6 - 10.8	**666 - 1,108**
940	4000 K	-, 18°, 24°, 36°, 60°	6 - 10.8	**684 - 1,137**

Luminous flux range per version

Minimum 648 lm / 6 W / 930 / DL3664CL001ON

Maximum 1,137 lm / 10.8 W / 940 / DL3677CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >