
MINOR S 2F LED

1,890 variants



Dimensions



Available colours

White | Black | Grey | Gold | Chrome | Nickel

It suits homes, offices, hotels and commercial spaces where the ceiling needs to remain clean and the lighting should integrate quietly into the architecture. Beyond the 18°–60° beams, which cover different levels of concentration, the oval 25x60° beam is available for applications that need more reach in one direction. This allows the same product to support both classic directional lighting and more elongated coverage. Its medium scale offers more light quantity and a larger body than the simpler versions, while keeping a related appearance within the series. As the smaller version of the series, it suits areas that need a lighter visual presence without changing the design approach. Low glare combined with CRI90 makes it suitable for projects with high visual-comfort requirements, including offices, hospitality spaces and WELL or LEED-oriented applications. It is available in multiple finish options, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects. The recessed installation keeps the ceiling clean and allows the luminaire to work without drawing excessive attention. Body dimensions: 218×125×103 mm. The corresponding dimensions are listed for each variant.

LUMINAIRE POWER

12 - 21.6 W

LUMINAIRE LUMINOUS FLUX

1,296 - 2,274 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of MINOR S 2F LED.

Mounting position	**Ceiling Recessed**	Operating voltage	**2x34.6 V**
Housing	**Metal**	Power factor	**0.96**
Optic	**Safety Glass Clear**	Protection rating	**IP20 / IK05**
Light source	**COB LED**	Insulation class	**Class III**
Body dimensions	**125 × 218 × 103 mm**	Lifetime	**>60.000h L80B10@35°C**
Control Gear	**Remote Electronic Driver**	Operating temperature	**-10…+45°C**
Colour uniformity	**3 SDCM**	Operating humidity	**5…95%**
Ripple	**3**	Lighting direction	**Sideways**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams - (ASY), 18° (N), 24° (NM), 36° (M), 60° (XW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 99.8 - 114 lm/W | UGR longwise / parallel 12 - 17 / 12 - 23

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	-, 18°, 24°, 36°, 60°	12 - 21.6	**1,296 - 2,156**
935	3500 K	-, 18°, 24°, 36°, 60°	12 - 21.6	**1,332 - 2,215**
940	4000 K	-, 18°, 24°, 36°, 60°	12 - 21.6	**1,368 - 2,274**

Luminous flux range per version

Minimum 1,296 lm / 12 W / 930 / DL4623CL001ON

Maximum 2,274 lm / 21.6 W / 940 / DL4636CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >