
ANULUS 2F LED

1,512 variants



Dimensions



Available colours

White | Black | Grey | Chrome | Nickel | Anthracite

ANULUS 2F LED is a recessed ceiling luminaire with a metal body and 200 mm width, 175 mm height, 380 mm length. It suits homes, offices, hotels and commercial spaces where the ceiling needs to remain clean and the lighting should integrate quietly into the architecture. Its medium scale offers more light quantity and a larger body than the simpler versions, while keeping a related appearance within the series. Low glare combined with CRI90 makes it suitable for projects with high visual-comfort requirements, including offices, hospitality spaces and WELL or LEED-oriented applications. It is available in multiple finish options, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects. The recessed installation keeps the ceiling clean and allows the luminaire to work without drawing excessive attention.

LUMINAIRE POWER

25.6 - 93.2 W

LUMINAIRE LUMINOUS FLUX

2,915 - 10,062 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of ANULUS 2F LED.

Mounting position	**Ceiling Recessed**	Power factor	**0.96**
Housing	**Metal**	Protection rating	**IP20 / IK05**
Optic	**Safety Glass Clear**	Insulation class	**Class III**
Light source	**COB LED**	Lifetime	**>60.000h L80B10@35°C**
Body dimensions	**200 × 380 × 175 mm**	Operating temperature	**-10…+45°C**
Control Gear	**Remote Electronic Driver**	Operating humidity	**5…95%**
Colour uniformity	**3 SDCM**	Lighting direction	**Sideways**
Ripple	**3**	Accessories	**RING R111, SHADE R111, UV FILTER**
Operating voltage	**2x34.6 V**		

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 18° (N), 24° (NM), 36° (M), 60° (XW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 99 - 119.7 lm/W | UGR longwise / parallel 12 - 20 / 12 - 19

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	18°, 24°, 36°, 60°	25.6 - 93.2	**2,915 - 9,599**
935	3500 K	18°, 24°, 36°, 60°	25.6 - 93.2	**2,989 - 9,831**
940	4000 K	18°, 24°, 36°, 60°	25.6 - 93.2	**3,063 - 10,062**

Luminous flux range per version

Minimum 2,915 lm / 25.6 W / 930 / DL4925CL001ON

Maximum 10,062 lm / 93.2 W / 940 / DL4938CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >