
ANULUS SQUARE 1F LED

1,512 variants



Dimensions



Available colours

White | Black | Grey | Chrome | Nickel | Anthracite

ANULUS SQUARE 1F LED is a recessed ceiling luminaire with a metal body and 200 mm width, 175 mm height, 200 mm length. It suits homes, offices, hotels and commercial spaces where the ceiling needs to remain clean and the lighting should integrate quietly into the architecture. As the smaller version of the series, it keeps a lighter presence and can be combined with larger versions when different light levels are needed within the same project. It is available in multiple finish options, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects. The recessed installation keeps the ceiling clean and allows the luminaire to work without drawing excessive attention.

LUMINAIRE POWER

12.8 - 46.6 W

LUMINAIRE LUMINOUS FLUX

1,458 - 5,031 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of ANULUS SQUARE 1F LED.

Mounting position	**Ceiling Recessed**	Power factor	**0.96**
Housing	**Metal**	Protection rating	**IP20 / IK05**
Optic	**Safety Glass Clear**	Insulation class	**Class III**
Light source	**COB LED**	Lifetime	**>60.000h L80B10@35°C**
Body dimensions	**200 × 200 × 175 mm**	Operating temperature	**-10…+45°C**
Control Gear	**Remote Electronic Driver**	Operating humidity	**5…95%**
Colour uniformity	**3 SDCM**	Lighting direction	**Sideways**
Ripple	**3**	Accessories	**RING R111, SHADE R111, UV FILTER**
Operating voltage	**34.6 V**		

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 18° (N), 24° (NM), 36° (M), 60° (XW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 99 - 119.7 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	18°, 24°, 36°, 60°	12.8 - 46.6	**1,458 - 4,800**
935	3500 K	18°, 24°, 36°, 60°	12.8 - 46.6	**1,486 - 4,916**
940	4000 K	18°, 24°, 36°, 60°	12.8 - 46.6	**1,514 - 5,031**

Luminous flux range per version

Minimum 1,458 lm / 12.8 W / 930 / DL5037CL001ON

Maximum 5,031 lm / 46.6 W / 940 / DL5050CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >