HONOR M N0 LED

675 variants



Dimensions



Available colours

White **Black** **Grey** **Chrome** **Nickel**

HONOR M N0 LED is a recessed ceiling luminaire with an aluminium body and 200 mm diameter. It suits homes, offices, hotels and commercial spaces where the ceiling needs to remain clean and the lighting should integrate quietly into the architecture. As the medium version of the series, it offers more presence than the smaller versions without becoming visually heavy. It is available in white, black, grey, nickel and chrome finishes, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects. The recessed installation keeps the ceiling clean and allows the luminaire to work without drawing excessive attention.

LUMINAIRE POWER

12.9 - 34.2 W

LUMINAIRE LUMINOUS FLUX

1,187 - 3,188 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of HONOR M N0 LED.

Mounting position	**Ceiling Recessed**	Power factor	**0.96**
Housing	**Aluminium**	Protection rating	**IP20 / IK04**
Optic	**Safety Glass Clear**	Insulation class	**Class III**
Light source	**COB LED**	Lifetime	**>60.000h L80B10@35°C**
Body dimensions	**Ø 200 × 125 mm**	Operating temperature	**-10…+45°C**
Control Gear	**Remote Electronic Driver**	Operating humidity	**5…95%**
Colour uniformity	**3 SDCM**	Lighting direction	**Downwards**
Ripple	**3**	Accessories	**CONVERSIONKIT & BATTERY**
Operating voltage	**34.6 V**		

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH • ENEC • CB**

Options per version

Beams 45° (W), 60° (XW), 75° (XW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 80.6 - 96.7 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	45°, 60°, 75°	12.9 - 34.2	**1,187 - 3,042**
935	3500 K	45°, 60°, 75°	12.9 - 34.2	**1,217 - 3,115**
940	4000 K	45°, 60°, 75°	12.9 - 34.2	**1,247 - 3,188**

Luminous flux range per version

Minimum 1,187 lm / 12.9 W / 930 / DL5193CL001ON

Maximum 3,188 lm / 34.2 W / 940 / DL5202CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >